

# AvediaStream e3532

Supports 1080p 50/60 High Definition (HD) and Standard Definition (SD) encoding

MPEG-4 H.264 video encoding from devices with an HDMI™ output such as a Blu-ray Disc players and for encoding the output of digital signage systems and PCs

Supports multicast and unicast



## Technical Specifications

### Video Input

Single channel

HD AV, RGBHV

Resolutions supported:

525i 59.94Hz (HD AV only)

625i 50Hz (HD AV only)

720p 50Hz/59.94Hz/60Hz

1080i 50Hz/59.94Hz/60Hz

1080p 23.98Hz/24Hz/50Hz/59.94Hz/60Hz

### Video Encoding

H.264 encoding at constant or variable bitrate

525i/625i: Main Profile Level 3.0 (2Mbps - 10Mbps)

720p: High Profile Level 4.0 (4Mbps - 24Mbps)

1080i/1080p24: High Profile Level 4.0 (6Mbps - 24Mbps)

1080p50/60: High Profile Level 4.2 (6Mbps - 30Mbps)

### Audio Input

Unbalanced stereo

S/PDIF digital audio

HD AV Audio

### Audio Encoding

MPEG-1, Layer 2

Encoding bit rate 48Kbps – 384Kbps

Audio sampling rate 48KHz

AC3 audio pass through from S/PDIF

### IR Output

Control of AV source device

### Network Interface

802.3 10/100BaseT Ethernet

### Channel Streaming

Single program MPEG transport stream

RTP or UDP

IP multicast or one unicast address destination

Channel announcement using SAP/SDP

### Network Protocols

TCP, UDP, DHCP (client), IGMP

### Management

SNMP, TFTP, HTTP

Web management interface

Serial admin port

### Control User Interface

Automatic or manual multicast address selection

Configure channel name, number, group membership

Stream on boot

### Chassis Options

AvediaStream c1101 providing 1 Encoder

AvediaStream c1103 providing up to 3 Encoders

AvediaStream c1110 providing up to 10 Encoders

### Power Consumption

10W Typical (15W Max)

## More Information on MPEG Encoders

Encoder family product brochure

Encoder e2110, e2220, e2250, e2550, e3520 and e3550 Technical Specifications Datasheets

Chassis c1101, c1103 and c1110 Technical Specifications Datasheets

**Head Office:** Ridge Way, Hillend Industrial Park, Dalgety Bay, Dunfermline, UK, KY11 9JD

**t:** +44(0) 1383 828 250 **f:** +44(0) 1383 824 905 **w:** [www.exterity.co.uk](http://www.exterity.co.uk) **e:** [info@exterity.co.uk](mailto:info@exterity.co.uk)

© 2009 Exterity Ltd. All rights reserved. The Exterity Building IPTV logo, AvediaStream, AvediaServer, AvediaCentre and isocket are trademarks or registered trademarks of Exterity Ltd. The information and specification are subject to change without prior notice. Exterity tries to ensure that all information in this document is correct but does not accept liability for any error or omission. HDMI, the HDMI Logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.

