

Lumino360

Standard Definition Pan/Tilt/Zoom Camera

The Lumino360 SD PTZ camera is a high quality standard definition camera, with flexible operation of remote PTZ control and easy-to-use features.

The camera is equipped with 18 x optical zoom, a diagonal pan & tilt function and can be mounted upright or inverted, making the camera ideal for video conferencing, distance learning, training, security and more.



Features

- 18 x optical zoom
- 12 x digital zoom
- IR remote control
- Diagonal pan/tilt
- Low motion noise
- Continuous 360° pan
- Back light compensation
- Crisp image, accurate colours
- Sony-Visca compatible
- Manufactured to ISO9000

Technical

Video Signal	PAL	Operating Temperature	0° C - +40° C
Video Output	S-Video, Composite	Storage Temperature	-20° C - +60° C
Image Sensor	1/4 inch Sony CCD	Power	DC 12V, <10W consumption
Effective Pixels	752 (H) x 582 (V)	Dimensions - unpacked	156 x 137 x 140mm
Resolution	480 TVL, SD	Dimensions- packed	300mm x 290mm x 240mm
Shutter Speed	1 - 1/10,000 second	Weight - packed	2.75kg
Focus	Auto / Manual	Body colour	Black
Focal Length	F 1.4-F3.0, f=4.1 - 73.8	Components Supplied	Camera, IR Remote, Manual, 240V-AC/12V-DC PSU with 1m DC cable
H. Viewing Angle	48°	Extra Cables Supplied	Fig.8 AC cable (1m), S-Video (3m), Composite/RCA (3m)
Operational Position	Upright or Inverted	Optional Cables	3m RS232 main, 5m Rs232 extension, Custom RS232, 2m RS485
Ceiling Plate	Optional	Optional Brackets	Ceiling, Wall, Vacuum, Pipe/Beam, Multi-pivot or Multi-arm
Pan Angle	360° continuous	Optional Accessories	Wide-angle lens (Hama, 0.5x, M37 thread, silver, 54g)
Pan Speed	-0.1° - 200° /sec	Warranty	1 year Bronze (RTB Wokingham, UK)
Sweep Angle	180° continuous	Extended Warranty	3 year Bronze, 1-3 years Gold (Advance Swap)
Sweep Speed	-0.1° - 200° /sec		
Tilt Angle	-30° - 90°		
Tilt Speed	0.1° - 150° /sec		
Preset Positions	64		
Control Interface	RS485/422, RS232		
Control Protocol	Sony VISCA		